The Town of Millinocket One Ton Truck Specifications

August 22, 2024

<u>Powertrain</u>

Engine:	8-cylinder gasoline
Transmission:	Heavy Duty Automatic/tow haul mode
Chassis:	4x4 GVWR 14,000 lbs. min. Dual Rear wheel configuration. Locking rear Differential. Fenders mounted over rear wheels.

Wheels and Tires

Tires:	Standard Steel Belted Radials
Rims:	Standard metal rims
Spare:	Full size mounted under bed, or included with chassis.
<u>Brakes</u>	Standard anti-lock brakes with traction and stability control.
	Trailer Brake Control.
<u>Tow Package</u>	2" Hitch and Receiver with D-Rings and 4/7 pin trailer wire harness
<u>Cab</u>	Regular Cab, Cloth Seats, AM/FM Radio, Mounted Fire Extinguisher located behind seat, Air Conditioning and heat, All-season rubber mats, power steering, extendable side view power mirrors with heat, power windows, 2-way Motorola radio provided by Whitten's Two-Way in Brewer. Spare upfitter electrical switches. Vent shades on doors. Heavy duty, replaceable seat covers.

- Electrical70 -amp/hr maintenance free Dual Batteries, 220 Amp HeavyDuty Alternator Factory installed emergency light control.Spare upfitter switches
- *Exterior* Color Gray or Silver
- *GVW* 14,000 lbs. min.
- LightingFactory installed emergency light control, LED body lights, 2
strobes one on each rear side of dump body, 2 grille or mirror
mounted, forward facing strobes on separate switch, 1 Whelen
Responder LP mini light bar, installed on head board of dump
body.
- Dump Body9' stainless steel with cross members, headboard shall have
rear view slotted cutout, Standard tail gate, electrically
operated hydraulic unit with in cab controls, Heavy duty scissor
life with min. 5" hydraulic cylinder, manual load w.wind
deflector and asphalt tarp.
- <u>Plow Equipment</u> Fisher V-Extreme 9.5' with snow deflector, hand held controller.
 - Service and shop manuals for truck & engine including parts and electrical drawings required.

<u>Warranty</u> Quote extended plan